Master Intercom

Picture	Model	Standard Voltage	Voltage Range	Collocation	Location	Max Operating Channel	Max Operating Distance
	MT-601-1	DC 6V	DC 4.5V-15V	CP-601-2	Control Room	1 channel	300m
	MT601-2	DC 6V	DC 4.5V-15V	CP-601-2	Control Room	1 channel	300m
	MT-610-1	DC 6V	DC 4.5V-15V	CP-610-2	Control Room	10 channel	300m
	MT-1201-1	DC 12V	DC 8.4V-18V	CP-1210-2	Control Room	1 channel	300m
	MT-1210-1	DC 12V	DC 8.4V-18V	CP-1210-5	Control Room	10 channel	300m
	MT-2406-2	DC 24V	DC 14V-30V	CP-2406-2	Control Room	6 channel	1000m

Car Slave Intercom

Picture	Model	Standard Voltage	Voltage Range	Collocation	Location	Max Operating Channel	Max Operating Distance
	CP-601-2	DC 6V	DC 4.5V-15V	MT-601-1 MT-601-2 TEL-606M-1	Car	1 channel	300m
	CP-610-2	DC 6V	DC 4.5V-15V	MT-601-1 MT-601-2 MT-612-2 TEL-606M-1	Car	10 channel	300m
	CP-1201-2	DC 12V	DC 8V-18V	MT-1201-1	Car	1 channel	300m
	CP-1210-5	DC 12V	DC 8V-18V	MT-1201-1 MT-1210-1 HP-1210-7	Car	10 channel	300m
	CP-2406-2	DC 24V	DC 14V-30V	MT-2402-2 MT-2406-2	Car	6 channel	1000m

Integrated Master Intercom

Picture	Model	Standard Voltage	Voltage Range	Collocation	Location	Standard Operating Channel	Max Operating Distance
	GMT-2420W10	DC 24V	DC 16V-DC 30V	CP-2406-2	Control Room	10/15/20/25/30/35/40/45/50	1000m

Remote Emergency Telephone

Picture	Model	Standard Voltage	Voltage Range	Collocation	Location	Max Operating Channel	Max Operating Distance
	TEL-606M-1	DC 6V	DC 4V-DC 13V	CP-601-X,CP-610-2	Control Room, Machine Room	6 channel	-

Telephone

Picture	Model	DTMF Dial Signal	Handset Function Conform	Open Frequency Alternating Risidtance	Tele-cable Lightning Stroke Test	Colour
	TEL-4801-3	0mile:HF:-6+2dBm LF:-8+2dBm 5mile:HF:>-21dBm LF:>21dBm	OREM-A Rule	≥100kΩ	Max voltage>800V	white